

Identity Registration Web Service V2 - Resources - Name

The name resource allows you to read and update source-independent names associated with person entities.

- [Attributes](#)
- [Actions](#)
 - [Reading a Record \(GET\)](#)
 - [Updating a Record \(POST\)](#)

Attributes

[IRWS Name Attributes](#) describes all the attributes of the Name resource, as well as which attributes must be defined when performing certain operations (read, update, etc.) on the resource.

Actions

Note: Your application may not be authorized for all of these actions.

Reading a Record (GET)

You can read a source record with the following HTTP request:

```
GET {baseurl}/name/{identifier}
```

where *{baseurl}* is the [base URL](#) for the service, and *{identifier}* is an institutional identifier for this record. The institutional identifier can be a RegID, UW Employee ID Number, or UW Student Number. No payload is required, and it will be ignored if provided.

Details on parameters and schemas are available in the [API Specification](#).

[IRWS Name Attributes](#) provides detailed descriptions of attributes.

Updating a Record (POST)

You can update a source record with the following HTTP request:

```
POST {baseurl}/name/{identifier}
```

where *{baseurl}* is the [base URL](#) for the service, and *{identifier}* is an institutional identifier for this record. The institutional identifier can be a RegID, UW Employee ID Number, or UW Student Number.

Details on parameters and schemas are available in the [API Specification](#).

[IRWS Name Attributes](#) provides detailed descriptions of attributes.



Updates to the name resource may be made by either PUT or POST.