

Groups Webservice Get Effective Members

Get effective membership

Resource

- **GET** | **(root)/group/{group_id}/effective_member**

The **group_id** can be a group name (cn) or a regid.

Return

20 0	Group's effective membership <ol style="list-style-type: none">1. Content of the response contains one class "group".2. Other html is for browser formatting.3. Within the class "members" there is one "effective_member" for each member.4. Each "member" is also an anchor to the specific effective member
30 4	If-None-Match header matches group's ETag
40 4	Group not found

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
  "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en">
<head>
<meta http-equiv="Content-Type" content="application/xhtml+xml; charset=utf-8"/>
</head>
<body>
  <div class="group">
    Regid: <span class="regid">{regid}/span>
    <br/>
    <ul class="members">
      <li>
        <a rel="memberlink" class="effective_member" type="{type}"
          href="(root)/group/{regid}/effective_member/{member_id}">{member_id}</a>
      </li>
      <!-- Additional (li) for each member -->
    </ul>
  </div>
</body>
</html>
```

Conventions

{text} : replace {text} with specific content

(root) : Webservice URL base

(type) : uwnetid | group | dns | eppn

Notes

- The effective membership is a gathered resource and cannot be PUT nor DELETED.