

Groups Webservice Get Members

Get membership

Resource

- **GET** `(root)/group/{group_id}/member`

The `group_id` can be a group name (cn) or a regid.

Return

200	Group's direct membership
	<ol style="list-style-type: none">1. Content of the response contains one class "group".2. Other html is for browser formatting.3. Within the class "members" there is one "member" for each member.4. Each "member" is also an anchor to the specific member
	<pre><!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN" "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd"> <html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en"> <head> <meta http-equiv="Content-Type" content="application/xhtml+xml; charset=utf-8"/> </head> <body> <div class="group"> Regid: {regid}
 <ul class="members"> {member_id} <!-- Additional (li) for each member --> </div> </body> </html></pre>
304	If-None-Match header matches group's ETag
401	No permission to view membership
404	Group not found

Conventions

{text} : replace {text} with specific content

(root): Webservice URL base

(type) : uwnetid | group | dns | eppn | uwwi

Notes

- The response always includes an ETag header, which can be used on subsequent GETs and must be used on subsequent updates or deletes.