

# Groups Webservice Add Member

## Add a member

### Resource

- **PUT** | **(root)**/group/{group\_id}/member/{member\_id}
- **PUT** | **(root)**/group/{group\_id}/member/{member\_id},{member\_id},...

The **group\_id** can be a group name (cn) or a regid.  
A set of members can be specified with a comma-separated list.

GWS tries to guess the type of identifier you enter. You may express the type specifically using a type preface.

- **u**: UWNetID
- **e**: ePPN
- **g**: group id
- **d**: DNS name
- **w**: UWWI computers

For example, **u:spud\_123** is a UWNetID, whereas **g:spud\_123** is a group name.

### Return

200	Member(s) added
304	If-None-Match header matches group's ETag
401	Not authorized
404	Group not found

### Notes

- The response will be 404 **only** if the group is not found. If one or more members are not found, or if they are not in the dependency group, the response will be 200 and a **class="notfoundmembers"** element will be included, containing one "notfoundmember" element for each bogus member.

```
<span class="notfoundmembers">
  <span class="notfoundmember">member_id</span>
  ...
</span>
```

- The response always includes an ETag header, which can be used on subsequent GETs.

### Conventions

**{text}** : replace {text} with specific content

**(root)**: Webservice URL base

**(type)** : uwnetid | group | dns | eppn